

Steridyne®

0.2 µm VMV-grade Small Filter Cartridge (L model)

Description

Steridyne® VMV0.2 is a hydrophobic PVDF membrane filter optimized for critical air and gas applications. Designed for bidirectional flow, this sterilizing grade filter is well suited for applications requiring complete removal of bacteria and viruses from air and gas streams, such as fermenter inlet air and exhaust, sterile process air, and sterile venting of carboys, filling vessels, bioreactors and small product or intermediate tanks.

The Steridyne® VMV0.2 small flow element (SFE) filter cartridge is manufactured using high quality components that are nontoxic and biologically inert.

Materials of Construction

All components of the Steridyne® filter are either animal component free or in compliance with EMEA/410/01 Rev. 3 (EDQM 5.2.8 07/2011:50208), and US Code of Federal Regulations 9 CFR 94.18 and 21 CFR 189.5. These materials are listed for food contact use in the Code of Federal Regulations (CFR), Title 21, as below:

Membrane:	Polyvinylidene fluoride	CFR Title 21, 177.2510
Upstream support:	Polypropylene	CFR Title 21, 177.1520
Downstream support:	Polypropylene	CFR Title 21, 177.1520
Outer guard:	Polypropylene	CFR Title 21, 177.1520
Core:	Polypropylene	CFR Title 21, 177.1520
End caps:	Polypropylene	CFR Title 21, 177.1520
O-rings:	Typically Silicone	CFR Title 21, 177.2600
Sealing method:	Thermal bonding	

Pore Size	0.2 µm
Minimum Bubble Point	18 psi (1.24 bar), 60% IPA/40% water 17 psi (1.17 bar), 70% IPA/30% water
Maximum Diffusion Rate	2.5" (7 cm): 3.0 mL/min @ 15 psid (1.03 bar), 60% IPA/40% water 5.0" (13 cm): 6.4 mL/min @ 15 psid (1.03 bar), 60% IPA/40% water
Maximum WIT Rate	2.5" (7 cm): 0.1 mL/min water @ 20 psi (1.38 bar) 5.0" (13 cm): 0.2 mL/min water @ 20 psi (1.38 bar) <i>Specification can vary by instrumentation; consult Meissner.</i>
Typical Air Flow Rate	2.5" (7 cm): 3.85 scfm/psid (4.7 Nm ³ /hr @ Δp 50 mbar) 5.0" (13 cm): 8.33 scfm/psid (10.3 Nm ³ /hr @ Δp 50 mbar)
Bacterial Retention	>10 ⁷ per cm ² removal of <i>Brevundimonas diminuta</i> per ASTM F838
Operating Characteristics	
Operating temperature range:	32 °F to 100 °F (0 °C to 38 °C)
Maximum temperature rating:	180 °F @ 30 psid (82 °C @ 2.1 bar)
Maximum operating pressure:	80 psid @ 100 °F (5.5 bar @ 38 °C)
Maximum reverse pressure:	15 psid @ 100 °F (1.0 bar @ 38 °C)

Sterilization

Autoclave: 121 °C to 135 °C (15 to 30 psi, 1 to 2 bar), 30 to 60 minutes, ≥ 3 cycles.

In-line steam sterilized: 121 °C to 135 °C (15 to 30 psi, 1 to 2 bar), 30 to 60 minutes, ≥ 3 cycles.


Biological Safety

Steridyne® filters meet the requirements as specified in the current USP <88> Class VI plastics, physicochemical, oxidizable substances, and USP <87> cytotoxicity. No binders, adhesives or surfactants are used in the construction of Steridyne® filters. Filters comply with European Commission Regulation No 10/2011.

Quality Assurance

Steridyne® filters comply with the Food and Drug Administration Code of Federal Regulations, Title 21, Parts 210 and 211. Product is manufactured and packaged in a cleanroom facility that, through voluntary compliance, meets or exceeds FDA Good Manufacturing Practice Standards. To ensure product reliability, Meissner's Quality Assurance staff continually audits the manufacturing process for conformance to its Quality Management System. Each Steridyne® filter is integrity tested during manufacture and is clearly marked with filter type and lot number.

Ordering Guide



Additional information about this filter product is available in the Steridyne® Green Docs document at www.meissner.com/green-docs.

Viton and Teflon are registered trademarks of DuPont Dow Elastomers L.L.C. & The DuPont Company.
 Steridyne® is a registered trademark of Meissner Filtration Products.
 © 2020 Meissner Filtration Products, Inc. All rights reserved.